

T-GALA 2022

BALANCED PATCH AND MICROPHONE CABLE HELICALLY SCREENED

CU PE Pet-sp CU CU-SP PVC2



|| A || B || C || D || E || C || F ||

- A INNER CONDUCTOR PLAIN COPPER
- B INSULATION LOW DENSITY POLYETHYLENE
- C NON-MIGRATING SPIRAL POLYESTER TAPE
- D DRAIN WIRE PLAIN COPPER
- E SPIRAL SHIELD PLAIN COPPER
- F SHEATH SOFT MATT NON-CONTAMINATING POLYVINYL-CHLORIDE
 - COLOUR BLACK - RAL 9004

TEMPERATURE RANGE -20 °C / +80 °C

MECHANICAL DATA

	INNER CONDUCTOR		SHIELD COVERAGE	SHEATH	WEIGHT KG/KM	
	CONSTRUCTION	SECTION			COPPER	TOT
T-GALA 2022	2 x (7 x 0,20 mm)	2 x 0,22 mm ²	98%	ø 3,20 ± 0,10 mm	10,9	17,9

ELECTRICAL PROPERTIES at 20°C

	CAPACITANCE		CORES RESISTANCE	VOLTAGE	
	CORE TO CORE	CORE TO SHIELD		OPERATING	TEST
T-GALA 2022	84 pF/m	130 pF/m	82 Ohm/Km	300 Vca	2000 Vca

The producer reserves himself to make modification on the item without any notice.