



FABBRICA CAVI - ANTENNE - ACCESSORI TV



MPE 2022 SP

BALANCED MICROPHONE CABLE HELICALLY SCREENED

CU

PE

CU-SP

PVC2



A

B

C

D

- A** INNER CONDUCTOR PLAIN COPPER
- B** INSULATION LOW DENSITY POLYETHYLENE
..... COTTON
- C** SPIRAL SHIELD PLAIN COPPER
- D** SHEATH SOFT MATT NON-CONTAMINATING POLYVINYL-CHLORIDE
- COLOUR BLACK - RAL 9004

TEMPERATURE RANGE -20 °C / +80 °C

MECHANICAL DATA

	INNER CONDUCTOR		SHIELD COVERAGE	SHEATH	WEIGHT KG/KM	
	CONSTRUCTION	SECTION			COPPER	TOT
MPE 2022 SP	2 x (28 x 0,10)	2 x 0,22 mm ²	100%	ø 6,00 ± 0,10 mm	10,3	42,1

ELECTRICAL PROPERTIES at 20°C

	CAPACITANCE		CORES RESISTANCE	VOLTAGE	
	CORE TO CORE	CORE TO SHIELD		OPERATING	TEST
MPE 2022 SP	68 pF/m	130 pF/m	82 Ohm/Km	300 Vca	2000 Vca

The producer reserves himself to make modification on the item without any notice.